

L027AE

2x 1GbE RJ45, 2x 10GbE Multi-mode Fiber



PHYSICAL

Dimensions (W x H x D)	43.40 cm x 4.45 cm x 57.40 cm 17.09 in x 1.75 in x 22.60 in
Weight	12.41 kg (Unit) 18 kg (Gross)
ECCN	5A992
USHTS Code	8471.50.0150

ELECTRICAL

Max Potential Power	455 Watts (Max)
Heat Dissipation	1552.52 BTU/hr (Max)
AC Power Option	100 - 240 VAC (Input Voltage) 50 - 60 Hz (Line Frequency)

AC PSU Connector C14



DC Power Option Not qualified at this time

DC PSU Connector None available

ENVIRONMENTAL

Operating Conditions 10 to 35 °C (50 to 95 °F)
8% to 80% RH (non-condensing)

Storage Conditions -40 to 65 °C (-40 to 149 °F)
5% to 95% RH (non-condensing)

Noise Level 58 dBA (Max)

Electromagnetic Compliance EN 55024:2010, EN 55032:2015
EN 61000-3-2:2014
EN 61000-3-3:2013

Safety Compliance EN 60950-1:2006, EN 62368-1:2014
EN IEC 62368-1:2020, EN 62311:2008
IEC 60950-1:2005

SYSTEM

System Management iDRAC9 Enterprise

Storage Capacity 480GB Redundant Storage

I/O Interfaces 2x 1GbE RJ45
2x 10GbE SFP+ slots installed with 2x 10GbE Multi-mode Fiber Transceivers

PORT CONFIGURATION

